

Date: 14 May 2025

CORRIGENDUM-IV TO TENDER NO

No.: IISER/PUR/2080/PYS/IT/24-25

Sub: Supply and Installation of Supply, Installation and commissioning of Audio Visual Facility for six different rooms in Maths block IISER Tvm campus : reg

Ref: Tender Enquiry No. 2025_IISRT_854061_1

1. Technical corrigendum is placed at Annexure 1.
2. The due dates of the above mentioned tender is hereby extended as follows:-

Due Date: 19 May 2025 1500 Hrs

Date of opening: 20 May 2025 1530 Hrs

3. Bidders may quote accordingly.

Thanking You,

Yours Faithfully



14/5/25

Assistant Registrar (P&S)



PH.-0471 2778019,
EMAIL: purchasestores@iisertvm.ac.in

MARUTHAMALA.P.O VITHURA. P.O
THIRUVANANTHAPURAM 695551,
KERALA, INDIA
GST No.32AAAJI0299R1ZS

Annexure 1

Item	Recommendations
USB Camera Device Extender Set	M/s Kramer is allowed as one of the approved makes
Bulk and Patch Cables (HDMI, CAT6A, Speaker, Microphone, USB cables)	M/s Kramer is allowed as one of the approved makes
Cable cubby	One USB-A charging port is enough
4x3 USB-C/HDMI Switcher with Receiver	<ul style="list-style-type: none"> The input/output specification for the switcher may be read as "It should have two HDMI 2.0 along with USB 2.0 type B ports and two full featured USB-C 3.1 Gen 1 input ports. On the output side, Two HDMI 2.0 ports, one Cat transmitter output port for HDMI2.0 & USB2.0 and one analog audio ports" USB-C charging at 60W or above is permitted Occupancy sensor or I/O port for occupancy sensor connection. 24V power supply is not mandatory. OCS port is not mandatory at the receiver
Controller Button panel	<ul style="list-style-type: none"> M/s Kramer is allowed as one of the approved makes PoE via Ethernet port with network time protocol is not mandatory One or more Ethernet port with PoE is allowed. GPIO ports with 2 or more connections allowed
Cabling and termination charges and Installation, Commissioning, User Training, Charges Qty	Quantity is to be read as 1
85" or better 4k UHD Interactive Display	<ul style="list-style-type: none"> Read 'Brightness :390nit(w/o Glass, typ)' as 'Brightness 390nit(with or without Glass,Typ)' Read 'Haze:28%' as 'Haze:25% or more' RGB IN -1 stands removed Read 'Built in Audio Power:15Wx2 or better' as 'Built in Audio Power:10Wx2 or better'
85" or better 4k UHD Display	<ul style="list-style-type: none"> Panel Technology: IPS/VA is allowed Contrast Ratio of 4,000:1 is permitted The following stands removed – 'Color Depth: 10-bit, Conformal Coating for Dust and Humidity Protection, Inbuilt Graphics Supported: GPU Arm Mali T820 MP2 (650 MHz) or better'
4x2 USB-C/HDMI Switcher	<ul style="list-style-type: none"> USB-C charging at 60W or above is permitted Occupancy sensor or I/O port for occupancy sensor connection. 24V power supply is not mandatory.
Annexure C – Sr.No 29	<ul style="list-style-type: none"> Item Description to be read as "USB 3.2 A(M) to B(M), 6feet" Spec to be read as "USB 3.2 Type A male to type B male cable 6feet length . Supported Bandwidth: 5Gbps"
Annexure A – Sr.No 17	Item Description to be read as "Wall speaker 150 watts"
Annexure B – Sr.No 16	Item Description to be read as "Wall speaker 150 watts"



Amma Sadath
14/5/25

PH.-0471 2778019,
EMAIL: purchasestores@iisertvm.ac.in

MARUTHAMALA.P.O VITHURA. P.O
THIRUVANANTHAPURAM 695551,
KERALA, INDIA
GST No.32AAAJI0299R1ZS

Wireless Lapel mic system and Handheld wireless microphone system transmitters	Should have the option to insert 2 nos of AA battery and to have longer operational hours during lectures
20x PTZ camera for audience with mount	<ul style="list-style-type: none"> - M/s ATDSC to the approved as one of the makes - 1/2.8 inch High quality CMOS sensor is also allowed - 54.7° field of view is also allowed - SDI, Line in Interfaces stands removed - OEM Should have Warranty Portal in the website to check the Product warranty status stands removed
20 x zoom presenter tracking camera	<ul style="list-style-type: none"> - M/s ATDSC to the allowed as one of the approved makes - 1/3 inch High quality CMOS sensor is also allowed - 55.4° field of view is also allowed - Focal length f=5.2 - 94mm is also allowed - SDI Interfaces stands removed - NDI feature and support Minimum 4 Zones for preset tracking stands removed
Speakerphone	<ul style="list-style-type: none"> - M/s LIVEY is approved as one of the makes - OEM should have ISO 9001:2015 & 14001:2015 certification stands removed

Anwar Sadath
14/5/25



